

TITLE OF THE INVENTION

IMAGE PROCESSING APPARATUS AND IMAGE PROCESSING METHOD

CROSS-REFERENCE TO RELATED APPLICATIONS

This application claims the benefit of U.S.

5 Provisional Application No. 60/471,335, filed May 19,
2003.

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to an image
10 processing apparatus and an image processing method,
which are used in an image forming apparatus, such as a
printer or a digital copying machine, wherein an image
signal produced by reading an image of an original by
image input means such as a scanner is subjected to
15 image processing such as tone processing, and the
processed image is printed out onto paper by binary
image output means of, e.g., an electrophotographic
type.

2. Description of the Related Art

20 In a conventional tone process wherein output
pixel values (binary) are determined by comparison with
threshold values that change cyclically as in a regular
pattern dither method, only a screen pattern, which is
output as an image and varies in a simple fashion
25 relative to an input image signal, is produced. It is
not possible, therefore, to form a screen pattern that
varies in a complex fashion in accordance with a gray

level of the input image signal. In addition, an enormous memory capacity is required to store binary screen patterns corresponding to all input image signals.

5

BRIEF SUMMARY OF THE INVENTION

The object of an aspect of the present invention is to provide an image processing apparatus and an image processing method, which can perform a tone process by forming, with use of a small-capacity
10 memory, a variety of binary screen patterns which vary in a complex fashion in accordance with gray levels.

According to an aspect of the present invention, there is provided an image processing apparatus comprising: first signal generating means for
15 generating a first signal on the basis of an input image signal; first memory means for storing a plurality of pattern data; read-out means for reading out first and second patterns stored in the first memory means, in accordance with the first signal
20 generated from the first signal generating means; third pattern producing means for producing a third pattern on the basis of the first and second patterns read out by the read-out means; second signal generating means for generating a second signal on the basis of the
25 image signal; second memory means for prestoring a fourth pattern; fifth pattern generating means for generating a fifth pattern on the basis of the fourth

pattern stored in the second memory means and the
second signal generated from the second signal
generating means; position calculation means for
calculating an intra-pattern position signal indicative
5 of a position within the patterns; and interpolation
calculation means for calculating, in accordance with
the intra-pattern position signal calculated by the
position calculation means, an output pixel value on
the basis of a first pixel value within the first
10 pattern corresponding to the intra-pattern position, a
second pixel value within the third pattern
corresponding to the intra-pattern position, and a
third pixel value within the fifth pattern
corresponding to the intra-pattern position.

15 According to another aspect of the present
invention, there is provided an image processing method
comprising: generating a first signal on the basis of
an input image signal; prestoring a plurality of
pattern data; reading out first and second patterns
20 from the plurality of pattern data in accordance with
the generated first signal; producing a third pattern
on the basis of the read-out first and second patterns;
generating a second signal on the basis of the image
signal; prestoring a fourth pattern; generating a fifth
25 pattern on the basis of the prestored fourth pattern
and the generated second signal; calculating an intra-
pattern position signal indicative of a position within

the patterns; and calculating, in accordance with the
calculated intra-pattern position signal, an output
pixel value on the basis of a first pixel value within
the first pattern corresponding to the intra-pattern
5 position, a second pixel value within the third pattern
corresponding to the intra-pattern position, and a
third pixel value within the fifth pattern
corresponding to the intra-pattern position.

Additional objects and advantages of an aspect of
10 the invention will be set forth in the description
which follows, and in part will be obvious from the
description, or may be learned by practice of the
invention. The objects and advantages of an aspect of
the invention may be realized and obtained by means of
15 the instrumentalities and combinations particularly
pointed out hereinafter.

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWING

The accompanying drawings, which are incorporated
in and constitute a part of the specification,
20 illustrate presently preferred embodiments of the
invention, and together with the general description
given above and the detailed description of the
preferred embodiments given below, serve to explain the
principles of an aspect of the invention.

25 FIG. 1 is a block diagram showing an internal
structure of an image processing apparatus according to
a first embodiment of the present invention;

FIG. 2 illustrates the outline of a process for generating a difference pattern DF and an interpolation pattern IP;

FIG. 3 is a flow chart illustrating an image
5 process in the image processing apparatus;

FIG. 4 is a block diagram showing an internal structure of an image processing apparatus according to a second embodiment of the present invention; and

FIG. 5 is a block diagram showing an internal
10 structure of an image processing apparatus according to a third embodiment of the present invention.

DETAILED DESCRIPTION OF THE INVENTION

Embodiments of the present invention will now be described with reference to the accompanying drawings.

15 FIG. 1 shows the structure of a digital copying machine having an image processing apparatus according to a first embodiment of the present invention. The digital copying machine comprises image input means 100 such as a scanner, an image processing apparatus 1, and
20 image output means 200 such as a printer.

The image processing apparatus 1 comprises screen pattern select signal generating means 11, interpolation signal generating means 12, a screen pattern table 13 & screen pattern table read-out means
25 14, difference pattern DF producing means 15, an interpolation order pattern table 16 & interpolation pattern generating means 17, intra-pattern position

calculation means 18, and interpolation calculation means 19.

5 The image processing apparatus 1 performs a tone process according to the present embodiment for an input image signal P7, which has undergone image processing (not illustrated) such as image-quality adjustment and compression/decompression in the preceding stage of the above-described structure.

10 The screen pattern table 13 stores a plurality of screen patterns, $S[i]$ $i=0$ to $N-1$. Each screen pattern $S[i]$ is a table having $n \times m$ pixels, to which "0" or "1" is assigned. Value "0" indicates a white pixel, and value "1" indicates a black pixel. Coordinates in the screen pattern are expressed by (xla, yla) , $0 \leq xla \leq n-1$, $0 \leq yla \leq m-1$. The coordinates (xla, yla) in the i -th screen pattern are expressed by $S[i](xla, yla)$.

15 In the screen pattern table 13, screen patterns are set or changed by a CPU (not shown).

20 The screen pattern select signal generating means 11 generates a screen pattern select signal i , which is used to select screen patterns $S[i]$ and $S[i+1]$ on the basis of the input image signal P7. In the present embodiment, the input image signal P7 is an 8-bit signal. High-order bits P7U of the input image signal P7 are assigned to the screen pattern select signal i . For example, if high-order 5 bits are "P7U", $i = 0$

25

to 31.

The interpolation signal generating means 12 generates an interpolation signal that is used to generate an interpolation pattern on the basis of the input image signal P7. In this embodiment, low-order bits P7L of the input image signal P7 are assigned to the interpolation signal. For example, if low-order 3 bits are "P7L", $P7L = 0$ to 7.

The screen pattern table read-out means 14 reads out screen patterns $S[i]$ and $S[i+1]$ corresponding to the screen pattern select signal i .

FIG. 2 shows examples of screen pattern $S[i]$ and screen pattern $S[i+1]$.

The difference pattern DF producing means 15 receives the read-out screen pattern $S[i]$ and screen pattern $S[i+1]$ and produces a difference pattern $DF(xla, yla)$ on the basis of the following equation:

$$\begin{aligned} DF(xla, yla) \\ = S[i](xla, yla) \text{ EXOR } S[i+1](xla, yla) \end{aligned}$$

where EXOR is Exclusive OR.

FIG. 2 shows an example of the difference pattern DF.

The interpolation order pattern table 16 shows the order in which a binary interpolation pattern IP is formed two-dimensionally in accordance with the interpolation signal P7L.

FIG. 2 shows an example of the interpolation order

pattern table $Od(xla, yla)$ 16. In this example, the interpolation order pattern table $Od(xla, yla)$ has the same size as the screen pattern. Values indicative of the order of 0 to $nm-1$ are assigned to the respective
5 pixels in the interpolation order pattern table $Od(xla, yla)$.

The interpolation order pattern in the interpolation order pattern table 16 is set or changed by the CPU (not shown).

10 Based on the interpolation signal $P7L$ and interpolation order pattern table $Od(xla, yla)$ 16, the interpolation pattern generating means 17 generates an interpolation pattern $IP(xla, yla)$ according to the following processing:

```
15      dj = (2^3)/(n*m) * P7L;
      for(xla=0;xla<n;xla++){
          for(yla=0;yla<m;yla++){
              if(dj>Od(xla,yla)){IP(xla,yla)=1;}
              else{IP(xla,yla)=0;}
20      }
    }
```

FIG. 2 shows an example of the interpolation pattern $IP(xla, yla)$.

The intra-pattern position calculation means 18
25 calculates an intra-pattern position (xl, yl) on the basis of image coordinates (main-scan coordinate x , sub-scan coordinate y) according to the following

equations:

$$x_1 = (x+y/m*xds)\%n$$

$$y_1 = y\%m$$

5 where xds indicates a skew in the screen pattern main-scan direction, which is used to provide a screen angle.

The interpolation calculation means 19 produces, based on the following equation, a tone process output (binary signal) $P8=0$ or 1 , which is determined from a screen pattern that is obtained by spatially
10 interpolating $S[i]$ and $S[i+1]$:

$$P8 = S[i](x_1, y_1) \text{ EXOR } (DF(x_1, y_1) \text{ AND } IP(x_1, y_1)).$$

The image processing in the image processing apparatus 1 with the above structure is described
15 referring to the flow chart of FIG. 3.

The screen pattern select signal generating means 11 generates a screen pattern select signal i on the basis of the input image signal $P7$ delivered from the image input means 100 (ST1).

20 At the same time, the interpolation signal generating means 12 generates an interpolation signal $P7L$ on the basis of the input image signal $P7$ delivered from the image input means 100 (ST2).

Subsequently, the screen pattern table read-out
25 means 14 reads out screen patterns $S[i]$ and $S[i+1]$ corresponding to the screen pattern select signal i that has been generated by the screen pattern select

signal generating means 11 (ST3).

The difference pattern DF producing means 15 produces a difference pattern DF on the basis of the screen pattern $S[i]$ and screen pattern $S[i+1]$ read out
5 by the screen pattern table read-out means 14 (ST4).

Based on the interpolation signal P7L generated from the interpolation signal generating means 12 and the interpolation order pattern table 16, the interpolation pattern generating means 17 generates an
10 interpolation pattern IP (ST5).

The intra-pattern position calculation means 18 calculates the intra-pattern position (x_l , y_l) on the basis of image coordinates (main-scan coordinate x , sub-scan coordinate y) (ST6).

15 Finally, the interpolation calculation means 19 produces a binary signal P8, which is determined from the input screen pattern $S[i]$, difference pattern DF, interpolation pattern IP and intra-pattern position (x_l , y_l) (ST7).

20 In this manner, the input image signal P7 from the image input means 100 is subjected to the tone process in the image processing apparatus 1 and output to the image output means 200 as the binary signal P8.

The image output means 200 produces an image on
25 the paper on the basis of the binary signal P8.

A second embodiment of the invention will now be described.

FIG. 4 shows the structure of an image processing apparatus 2 according to the second embodiment.

The image processing apparatus 2 comprises high-order-bit/low-order-bit separation means 21, a screen pattern table 22, screen pattern table read-out means 23, a difference pattern table 24 & difference pattern table read-out means 25, an interpolation order pattern table 26 & interpolation pattern generating means 27, intra-pattern position calculation means 28, and interpolation calculation means 29.

The image processing apparatus 2 of this embodiment executes the tone process after the input image signal P7 is subjected to image processing (not shown) such as image-quality adjustment and compression/decompression in the preceding stage of the above-described structure.

In the second embodiment, the difference pattern DF producing means 15 shown in FIG. 1 is configured as a table in advance. In the first embodiment, the difference pattern DF is generated from the screen patterns $S[i]$ and $S[i+1]$. In the second embodiment, difference patterns corresponding to the screen pattern select signal i are prestored in the difference pattern table $DF[i](x1a, y1a)$ 24.

The high-order-bit/low-order-bit separation means 21 produces high-order bits P7U of the input image signal P7, which is an 8-bit signal, as a screen select

signal i, and also produces low-order bits P7L of the input image signal P7.

The screen pattern table 22 and screen pattern table read-out means 23 are the same as the screen pattern table 13 and screen pattern table read-out means 14, so a description thereof is omitted.

The difference pattern table read-out means 25 refers to the difference pattern table 24 and reads out the difference pattern DF[i] corresponding to the screen pattern select signal i.

In the difference pattern table 24, difference patterns are set or changed by the CPU (not shown).

The interpolation order pattern table 26 and interpolation pattern generating means 27 are the same as the interpolation order pattern table 16 and interpolation pattern generating means 17, so a description thereof is omitted.

The intra-pattern position calculation means 28 is the same as the intra-pattern position calculation means 18, so a description thereof is omitted.

The interpolation calculation means 29 produces, based on the following equation, a tone process output (binary signal) P8=0 or 1:

$$P8 = S[i](x1,y1) \text{ EXOR } (DF(x1,y1) \text{ AND } IP(x1,y1)).$$

In this manner, the input image signal P7 from the image input means 100 is subjected to the toning process in the image processing apparatus 2 and output

to the image output means 200 as the binary signal P8.

The image output means 200 produces an image on the paper on the basis of the binary signal P8.

5 A third embodiment of the invention will now be described.

FIG. 5 shows the structure of an image processing apparatus 3 according to the third embodiment.

The image processing apparatus 3 comprises screen pattern select signal generating means 31,
10 interpolation signal generating means 32, a screen pattern table 33 & screen pattern table pixel read-out means 34, an interpolation order pattern table 35 & interpolation pixel value output means 36, intra-pattern position calculation means 37, and
15 interpolation calculation means 38.

The image processing apparatus 3 of this embodiment executes the tone process after the input image signal P7 is subjected to image processing (not shown) such as image-quality adjustment and
20 compression/decompression in the preceding stage of the above-described structure.

The screen pattern select signal generating means 31, interpolation signal generating means 32, screen pattern table 33, interpolation order pattern table 35
25 and intra-pattern position calculation means 37 are the same as those in the first embodiment shown in FIG. 1, so a description thereof is omitted.

The screen pattern table pixel read-out means 34 refers to the screen pattern table 33, and outputs a pixel value $S[i](x_l, y_l)$ and a pixel value $S[i+1](x_l, y_l)$ in the two screen patterns $S[i]$ and $S[i+1]$ corresponding to the screen pattern select signal i , these pixel values being associated with output coordinates (x_l, y_l) delivered from the intra-pattern position calculation means 37.

The interpolation pixel value output means 36 outputs an interpolation pixel value $IP(x_y, y_l)$ corresponding to the intra-pattern pixel position (x_l, y_l) on the basis of the following equation:

```
dj = (2^3)/(n*m) * P7L;  
if(dj>Od(xl,y1)){IP(xl,y1)=1;}  
else{IP(xla,y1a)=0;}
```

The interpolation calculation means 38 calculates a binary signal $P8$ by a logic operation on the basis of the pixel value $S[i](x_l, y_l)$, pixel value $S[i+1](x_l, y_l)$ and interpolation pixel value $IP(x_l, y_l)$.

An example of the logic formula for calculating the output value $P8$ is:

```
P8 = (S[i](xl,y1) and S[i+1](xl,y1)) or  
(S[i](xl,y1) and IP(xl,y1)) or ((not S[i](xl,y1)) and  
S[i+1](xl,y1) and IP(xl,y1)).
```

In this manner, the input image signal $P7$ from the image input means 100 is subjected to the tone process in the image processing apparatus 3 and output to the

image output means 200 as the binary signal P8.

The image output means 200 produces an image on the paper on the basis of the binary signal P8.

As has been described above, according to the
5 embodiments of the present invention, only the pattern
information corresponding to a specific signal within
the signal range is stored, and two upper and lower
screen patterns corresponding to the input image signal
value are spatially interpolated where necessary.
10 Thereby, the binary screen pattern for the input image
signal value can be generated.

The intra-pattern position (x1, y1) is calculated
on the basis of the main-scan and sub-scan coordinates
(x, y), and the corresponding values in the inter-
15 polated binary screen pattern are read out and output.

In the above embodiments, the digital copying
machine having the image processing has been described
by way of example. However, this invention is also
applicable to printers.

20 In addition, in the above embodiments, the scanner
has been described as an example of the image input
means. Alternatively, image data may be received from
an external device.

Additional advantages and modifications will
25 readily occur to those skilled in the art. Therefore,
the invention in its broader aspects is not limited to
the specific details and representative embodiments

shown and described herein. Accordingly, various modifications may be made without departing from the spirit or scope of the general inventive concept as defined by the appended claims and their equivalents.